



## CAV TV Transmitter

### MAIN FEATURES:

- Rack 19" 2U (5W-15W), 3U (50W-100W)
- 115/230Vac 50/60Hz Power Supply
- Indication of the main parameters on LCD display
- Alarm Thresholds for FWD Power, REF Power and Temperature
- Power Supply Input on IEC box with double fuse on the check
- RF Output with N connector on the rear
- Video Input with BNC connector on the front panel
- Audio Input with XLR connector on the front panel
- IF Link with SMB connector on the front panel
- Level adjustment (Video, Audio, SC) with multi-turn trimmer on front panel
- Class AB three-cell pre-corrector, selectable from front panel
- Automatic or Manual Gain Control on front panel
- Multifunction Display with two selection keys and buzzer
- Remote Control by wired or serial (RS232) connection

The TV Transmitters belonging to the CAV series have both a compact size and a pleasant and functional look. How does the Cav reach this goal?

The mother board is completely built in SMD technology and mounted by automatic machine to obtain high level of reliability.

The filter and amplification stage has been made compact, while keeping a good ventilation to limit working temperature, by mounting it all on a single heat sink with a bent steel conveyor.

All connectors and controls placed on the front panel are directly connected to the mother board.

The connections between the mother board and the control board are made through a single 20-pin connector.

All wiring between the mother board and the other sections of the CAV is made with detachable connectors (see clamps for power supply and control of the final stage) to make repair easier.

The output connector of the transmitter, the air inlet of the cooling system of the final stage, the power supply box including the main switch and fuses, the telemeasuring connector and the external reference input, if any, have been placed on the back of the CAV.

The user interface has been kept simple and intuitive with the use of an alphanumeric display and only two push-buttons. All the functions have been remoted by the RS232 rear panel connector.



▲ CAV 2U Rear panel

# Technical characteristics



**CAV TV Transmitter**

## MODELS

	5W	15W	50W	100W
UHF	CAV/5U	CAV/15U	CAV/50U	CAV/100U
VHF	CAV/5V	CAV/15V	CAV/50V	CAV/100V

## OPTIONS

- Dual Sound (See TV Stereo Coder)
- High Stability
- Output Filter

## RF SECTION

Frequency Range	VHF I, VHF III, UHF
Output Power	5W, 15W, 50W, 100W
Output Power Control	Automatic or Manual (switch-selectable)
I.M.D.	< -60dB (with IF Pre-corrector)
Spurious and Harmonics Level	< -60dB
RF Output Impedance	50Ω
RF Output Connector	N Female
Intermediate Frequency	38.9 or 45.75MHz (on request)
IF Output Level	-15dBm

## AUDIO SECTION

Input	600Ω / 10kΩ balanced
Nominal Level	2.2Vpp, -10dB ± +6dB
Pre-emphasis	Flat, 50μs, 75μs
Low Pass Filter	15kHz, 100kHz
Limitation Circuit	Δnom +1dB
Frequency Response	≤ 0.5dB
THD	≤ 0.5%
Intermodulation	d2 ≤ -60dB, d3 ≤ -60dB
S/N FM CCIR Ratio	≥ 60dB weighted ≥ 60dB unweighted (ref. 50kHz)
S/N AM Ratio	≥ 60dB asynchronous ≥ 50dB synchronous (ref. 100%)
IF	30.5MHz ... 41.25MHz
IF Level (on external link)	Adjustable

## VIDEO SECTION

Input	75Ω
Nominal Level	1Vpp ±6dB
Return Loss	≥ 30dB up to 5MHz
DC Recovery	Clamped to back porch
White Limitation	90% ... 115% non affecting crominance
Group Delay Pre-corrector	8 Cells
Group Delay	≤ 50ns (with professional vestigial filter)
Frequency Response	≤ ±0.5dB
Differential Gain	≤ ±5%
Differential Phase	≤ ±5°
Luminance Non-Linearity	≤ 5%
S/HUM Ratio	≥ 45dB weighted
S/N Ratio	≥ 65dB weighted, ≥ 55dB unweighted
Black Level Variation	≤ 2%
2T K Factor	≤ 1%
ICPM	< 3°
IF	32.7MHz ... 45.75MHz
IF Level (on external link)	-15dBm ... -10dBm

## LOCAL OSCILLATOR SECTION

Frequency	50MHz ... 900MHz split between band I, III, IV/V
Offset	±32kHz max
Frequency Stability	2.5ppm (0.05ppm with HIGH STABILITY option)
External Reference	5MHz
S/N FM CCIR Ratio	≥ 60dB weighted (ref. 35kHz)

## GENERAL

Power Supply	115/230V <sub>AC</sub> , ±10%, 50/60Hz
Cabinet	Rack 19"-2U (5W-15W), 3U (50W-100W)
Weight	9kg (2U), 15kg (3U)
Ambient Temperature	-5°C to +45°C
Humidity	20% - 90%
Remote Control	Wired and RS232

*These specifications are subject to change without notice*



P.O. Box 207 Geebung  
Brisbane Australia 4034  
Ph: +61 7 3504530 Fax: +61 7 3315 4683  
info@n-com.com.au www.n-com.com.au



SS 96 km 113 Z.I.  
70027 PALO DEL COLLE (BA) ITALY  
Tel. +39.080.626755 (PBX) - Fax +39.080.629262  
elettronika@elettronika.it www.elettronika.it